

Boring Designation BI-PB-062-10

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Mobile District		SHEET 1 OF 2 SHEETS	
1. PROJECT MsCIP Barrier Island Restoration Petit Bois Pass- AL West				9. SIZE AND TYPE OF BIT N/A			
2. BORING DESIGNATION BI-PB-062-10		LOCATION COORDINATES E = 1,137,556 N = 249,860		10. COORDINATE SYSTEM/DATUM State Plane, MSE (U.S. Ft.)		HORIZONTAL NAD83 VERTICAL NAVD88	
3. DRILLING AGENCY Corps of Engineers - CESAM		CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Vibracore		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER Construction Solutions International, Inc.				12. TOTAL SAMPLES		DISTURBED 1 UNDISTURBED (UD) 0	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL		13. TOTAL NUMBER CORE BOXES			
		BEARING		14. WATER DEPTH 38 Ft.			
6. THICKNESS OF OVERBURDEN N/A				15. DATE BORING		STARTED 08-06-10 COMPLETED 08-06-10	
7. DEPTH DRILLED INTO ROCK N/A				16. ELEVATION TOP OF BORING -38.0 Ft.			
8. TOTAL DEPTH OF BORING 20.0 Ft.				17. TOTAL RECOVERY FOR BORING 100%			
				18. SIGNATURE AND TITLE OF INSPECTOR Chris Gillentine, Geologist			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	SAMPLE	LABORATORY RESULTS		
-38.0	0.0						
			SAND, poorly-graded, mostly fine to medium-grained sand-sized quartz, gray (SP)	A	Classification: SM Color: 2.5Y 5/2-grayish brown D50: 0.1421 mm % Fines: 18		
				NS			
-58.0	20.0						
			NOTES: 1. Soils are field visually classified in accordance with the Unified Soils Classification System. 2. NS = Sample not submitted for laboratory analysis from this interval. 3. Seafloor elevation calculated using sampling				

DRILLING LOG (Cont. Sheet)			INSTALLATION Mobile District		SHEET 2 OF 2 SHEETS
PROJECT MsCIP Barrier Island Restoration			COORDINATE SYSTEM/DATUM State Plane, MSE (U.S. Ft.)	HORIZONTAL NAD83	VERTICAL NAVD88
LOCATION COORDINATES X = 1,137,556 Y = 249,860			ELEVATION TOP OF BORING -38.0 Ft.		
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	SAMPLE	LABORATORY RESULTS
			vessel's fathometer water depth reading and applying NOAA tidal gauge data conversion factor.		