

# Boring Designation BI-PB-156-12

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Mobile District		SHEET 1 OF 1 SHEETS	
1. PROJECT MsCIP Barrier Island Restoration Petit Bois Pass- AL East				9. SIZE AND TYPE OF BIT N/A			
2. BORING DESIGNATION BI-PB-156-12		LOCATION COORDINATES E = 1,144,612 N = 253,193		10. COORDINATE SYSTEM/DATUM State Plane, MSE (U.S. Ft.)		HORIZONTAL NAD83 VERTICAL NAVD88	
3. DRILLING AGENCY Corps of Engineers - CESAM		CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Vibracore		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER American Vibracore Systems, Inc.				12. TOTAL SAMPLES		DISTURBED UNDISTURBED (UD) 0	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL		13. TOTAL NUMBER CORE BOXES			
		BEARING		14. WATER DEPTH 35.4 Ft.			
6. THICKNESS OF OVERBURDEN N/A				15. DATE BORING 12-19-12		STARTED COMPLETED 12-19-12	
7. DEPTH DRILLED INTO ROCK N/A				16. ELEVATION TOP OF BORING -35.1 Ft.			
8. TOTAL DEPTH OF BORING 15.6 Ft.				17. TOTAL RECOVERY FOR BORING 100%			
				18. SIGNATURE AND TITLE OF INSPECTOR Mike FitzHarris, Geologist			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	SAMPLE	LABORATORY RESULTS		
-35.1	0.0						
-36.7	1.6		SAND, poorly-graded, mostly fine to medium-grained sand-sized quartz, trace shell fragments, lt. gray (SP)	A	Classification: SP Color: 5Y 7/2-light gray D50: 0.2901 mm % Fines: 1.5		
-37.1	2.0		SAND, silty, mostly fine-grained sand-sized quartz, some silt, trace clay, trace shell fragments, brownish gray (SM)				
			CLAY, fat, mostly clay, trace shell fragments, medium to high plasticity, stiff, trace pockets of fine-grained sand, greenish gray (CH)	NS			
-50.7	15.6						
			NOTES: 1. Soils are field visually classified in accordance with the Unified Soils Classification System. 2. NS = Sample not submitted for laboratory analysis from this interval. 3. Seafloor elevation calculated using sampling vessel's fathometer water depth reading and applying NOAA tidal gauge data conversion factor.				