

Boring Designation BI-PBS-061-12

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Mobile District		SHEET 1 OF 1 SHEETS	
1. PROJECT MsCIP Barrier Island Restoration Petit Bois Pass-OCS East				9. SIZE AND TYPE OF BIT N/A			
2. BORING DESIGNATION BI-PBS-061-12		LOCATION COORDINATES E = 1,150,557 N = 236,916		10. COORDINATE SYSTEM/DATUM State Plane, MSE (U.S. Ft.)		HORIZONTAL NAD83 VERTICAL NAVD88	
3. DRILLING AGENCY Corps of Engineers - CESAM		CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Vibracore		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER American Vibracore Systems, Inc.				12. TOTAL SAMPLES		DISTURBED UNDISTURBED (UD) 0	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL		13. TOTAL NUMBER CORE BOXES			
		BEARING		14. WATER DEPTH 55 Ft.			
6. THICKNESS OF OVERBURDEN N/A				15. DATE BORING 11-16-12		STARTED COMPLETED 11-16-12	
7. DEPTH DRILLED INTO ROCK N/A				16. ELEVATION TOP OF BORING -54.9 Ft.			
8. TOTAL DEPTH OF BORING 11.2 Ft.				17. TOTAL RECOVERY FOR BORING 100%			
				18. SIGNATURE AND TITLE OF INSPECTOR Mike FitzHarris, Geologist			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	SAMPLE	LABORATORY RESULTS		
-54.9	0.0						
-57.1	2.2		SAND, poorly-graded, mostly fine-grained sand-sized quartz, trace shell fragments, gray (SP)	A	Classification: SP-SM Color: 5Y 6.5/1-gray D50: 0.2349 mm % Fines: 5.2		
-60.7	5.8		SAND, silty, mostly fine-grained sand-sized quartz, some silt, trace clay, trace shell fragments, gray (SM)	NS			
-63.1	8.2		CLAY, fat, mostly clay, little fine-grained sand-sized quartz, medium plasticity, gray (CH)				
-64.6	9.7		SAND, silty, mostly fine-grained sand-sized quartz, some silt, brown (SM)				
-66.1	11.2		SAND, poorly-graded, mostly fine-grained sand-sized quartz, trace silt, light brown (SP)				
			NOTES: 1. Soils are field visually classified in accordance with the Unified Soils Classification System. 2. NS = Sample not submitted for laboratory analysis from this interval. 3. Seafloor elevation calculated using sampling vessel's fathometer water depth reading and applying NOAA tidal gauge data conversion factor.				