

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1912002.400 Y=83996.200				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-11				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-27-99 11-27-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.0 Ft.			
9. TOTAL DEPTH OF HOLE 17.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.0	0					-29.0	0
			Light grey medium to fine quartz sand. 10 YR 7/1 (SP)	100	0.5		
-32.1	3.1		Light brown-brown fine sand, scattered small shell fragments. 10 YR 5/3-6/3 (SP)		4.0		2.5
-34.0	5.0		Light grey to white fine sand, thin layer of small shell fragments. 10 YR 8/1-7/1 (SP)	100	8.0	-34.0	5
						Layer of small shell fragments, 9.2-9.3 ft	
				100	13.0	-38.0	10
-43.5	14.5		Dark brown plastic mud, small shell fragments. 10 YR 4/3 (CL)	100		-44.0	15
-46.1	17.1					Medium-fine white quartz sand, 16.6-16.8	
						-46.1	17.5
						Composite 0-14.5 ft.	20
							22.5