

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1914995.600 Y=84982.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-18				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.DIII/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.0	.0					-29.0	0
			Light grey fine sand, scattered shell fragments. 10 YR 7/1 (SP)		0.5		
				100			2.5
-32.0	3.0		Medium grey fine quartz sand. 10 YR 6/1 (SP)		4.0		
						-34.0	5
-35.9	6.9		Light grey fine quartz sand. 10 YR 7/1 (SP)	100	8.0		7.5
-37.4	8.4		White fine quartz sand. 10 YR 8/1 (SP)				
						-39.0	10
-40.7	11.7		Light grey-white medium to fine sand. 10 YR 7/1 (SP)	100	12.0		12.5
						-44.0	15
-44.2	15.2		Light grey-white medium to fine sand, scattered whole shells. 10 YR 7/1 (SP)	100			17.5
-47.6	18.6					-47.6	20
							22.5
Composite 0-12.7 ft.							