

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1915015.100 Y=83008.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-1				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-24-99 11-24-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.2 Ft.			
9. TOTAL DEPTH OF HOLE 17.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.2	.0		Light grey fine quartz sand. 10 YR 7/1 (SP)		0.5	-27.2	0
				100			2.5
-31.4	4.2		Tan-brown fine quartz sand, small shell fragments, whole shells to 3/4 inch. 10 YR 5/2 (SP)		4.0	-32.2	5
				100	8.0		7.5
-37.0	9.8		Light grey medium to fine quartz sand. 10 YR 6/1 (SP)		12.0	-37.2	10
				100			12.5
-41.0	13.8		Light grey-white to fine quartz sand. 10 YR 8/1 (SP)		17.0	-42.2	15
				100		Whole shell, 1 inch. (15.1 ft.)	
-45.0	17.8					-45.0	17.5
							20
						Composite 0-17.8 ft.	22.5