

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1916956.900 Y=81989.000				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-24				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.3 Ft.			
9. TOTAL DEPTH OF HOLE 16.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.3	.0					-27.3	0
-28.5	1.2		White fine quartz sand, scattered shell fragments. 10 YR 8/1 (SP)		0.5		
			Light grey fine sand. 10 YR 7/1-7/3 (SP)	100			2.5
-30.7	3.4		Greyish-brown fine sand. 10 YR 5/2 (SP)		4.0		
-32.9	5.6		Light grey-light brown fine sand. 10 YR 7/1-7/3 (SP)			-32.3	5
				100	8.0		7.5
-37.9	10.6		Light brown fine sand. 10 YR 7/3 (SP)			-37.3	10
-38.9	11.6		Light grey fine sand. 10 YR 7/1 (SP)				12.5
-41.0	13.7		Dark brown fine sand. 10 YR 7/3 (SP)	100	14.0		
-41.5	14.2		White to pale brown fine sand. 10 YR 8/1-8/2 (SP)				15
-43.7	16.4					Dark grey plastic mud, 15.9-16.1	
						-43.7	17.5
							20
						Composite 0-16.4 ft.	22.5