

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1915972.700 Y=81020.500			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-25			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -28.2 Ft.			
9. TOTAL DEPTH OF HOLE 13.5 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-28.2	.0					-28.2
-28.7	.5		Light brown fine quartz sand. 10 YR 8/2 (SP)		0.5	
			Light grey medium to fine sand. 10 YR 7/1 (SP)	100		
-31.4	3.2		Grey fine quartz sand. 10 YR 5/1 (SP)		4.0	-32.7
-33.8	5.6		Light grey fine quartz sand. 10 YR 7/1 (SP)	88.75		Empty void, 4.9-5.3 ft
-35.1	6.9		Grey fine quartz sand. 10 YR 5/1 (SP)		8.0	Black peat nodule, 7.4 ft.
-36.4	8.2		Light grey fine sand. 10 YR 6/1 (SP)			-37.2
				100	12.0	
-41.7	13.5					-41.7
						Composite 0-13.5 ft.