

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1901129.400 Y=82931.500			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-27			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 11-25-99 11-25-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -27.6 Ft.			
9. TOTAL DEPTH OF HOLE 16.3 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-27.6	.0					-27.6
-28.7	1.1		Pale brown fine sand, worm tubes. 10 YR 8/2 (SP)		0.5	
			Light grey medium to fine sand. 10 YR 7/1 (SP)	100	3.0	
-32.3	4.7					Inclusion of plastic mud, 4.2 ft.
-33.1	5.5		Brownish-grey fine sand. 10 YR 5/2 (SP)			-32.6
-33.4	5.8		Dark grey plastic mud. 10 YR 4/1 (CL)			
-34.2	6.6		Brown fine sand, some mud. 10 YR 5/3 (SM)			
-35.4	7.8		Brown layers of sand and mud. 10 YR 5/3 (ML)	100		
			Light grey medium to fine sand. 10 YR 7/1 (SP)			
-37.8	10.2					-37.6
-38.5	10.9		Light brownish grey medium to fine sand. 10 YR 6/2 (SP)			
			White to light grey medium to fine sand. 10 YR 8/1 (SP)	100		
-43.9	16.3					-43.9
						Composite 0.0-5.0 ft.