

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1913978.500 Y=82010.100				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-29				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.5 Ft.			
9. TOTAL DEPTH OF HOLE 9.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.5	.0					-29.5	0
			Light tan-yellow fine quartz sand. 10 YR 8/2 (SP)		0.5		
-32.3	2.8			100			2.5
-33.1	3.6		Light grey fine quartz sand. 10 YR 7/1 (SP)		3.0		
			Light grey fine quartz sand, scattered small shell fragments. 10 YR 6/1			-34.5	5
-36.2	6.7						
			Light grey fine quartz sand. 10 YR 7/1 (SP)	100	7.0		7.5
-39.0	9.5					-39.0	10
							12.5
							15
							17.5
							20
						Composite 0-9.5 ft.	22.5