

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1914508.300 Y=85514.200				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-30				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-27-99 11-27-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.2 Ft.			
9. TOTAL DEPTH OF HOLE 11.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.2	.0					-26.2	0
-27.3	1.1		Pale brown medium to fine quartz sand. 10 YR 8/2 (SP)		0.5		
			Light grey medium to fine quartz sand. 10 YR 7/1 (SP)	100			2.5
-30.1	3.9		Light brownish grey medium to fine quartz sand. 10 YR 6/2 (SP)		4.0	-31.2	5
-32.3	6.1		Light grey medium to fine quartz sand. 10 YR 7/1 (SP)				7.5
-34.3	8.1		White medium quartz sand. 10 YR 8/1 (SP)	100	8.0		10
					10.0		
-37.4	11.2					-37.4	12.5
							15
							17.5
							20
						Composite 0-11.2 ft.	22.5