

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1915984.300 Y=82994.300				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-33A				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER C.DIII/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.2 Ft.			
9. TOTAL DEPTH OF HOLE 19.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.2	.0					-27.2	0
							2.5
							5
							7.5
-37.2	10.0						10
			White medium to fine quartz sand. 10 YR 8/1 (SP)		10.5	Decayed organic matter, 10.8-11.0 ft.	
-38.8	11.6		Light grey fine quartz sand. 10 YR 7/1 (SP)	100			12.5
					14.0		
						-42.2	15
-44.3	17.1		Grey fine quartz sand. 10 YR 6/1 (SP)	100	17.0		17.5
-45.8	18.7						
-46.5	19.3		Grey-dark grey medium quartz sand and shell fragments. 10 YR 5/1-4/1 (SP)			-46.8	20
-46.8	19.6		Yellow-brown plastic mud, shell fragments. 10 YR 6/4 (ML)				22.5
						Composite 10.0-18.7 ft.	