

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1913971.000 Y=82978.800			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-34			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 11-25-99 11-25-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -26.8 Ft.			
9. TOTAL DEPTH OF HOLE 13.9 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-26.8	.0					-26.8
			Light grey medium to fine sand, scattered large shell fragments, and decayed brown organic material. 10 YR 7/1 (SP)	100	0.5	
-31.0	4.2		White fine sand. 10 YR 8/1 (SP)	100	4.0	
				100	8.0	
-36.8	10.1					Layer of peat, 9.0-9.1 ft.
-37.5	10.7		Pale brown medium quartz sand. 10 YR 8/2 (SP)	100		
			White medium to coarse sand, large shell fragments. 10 YR 8/1 (SP)	100		
-40.7	13.9					Shell frags. 3/4-2 inches, 13.6-13.9
						Composite 0-13.9 ft.