



DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 2	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1915969.900 Y=83984.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-35A				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3      undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-25-99 11-25-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.8 Ft.			
9. TOTAL DEPTH OF HOLE 22.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.8	.0					-28.8	0
							2.5
							5
							7.5
							10
-40.8	12.0						12.5
			White medium to fine quartz sand, 10 YR 8/1 (SP)		12.5	Layer of decayed organic matter, 13.4 ft	
				100		Layer of crushed shell material, 14.7 ft	
-44.3	15.5		Light grey medium to fine quartz sand, 10 YR 7/1 (SP)		16.0		15
-46.1	17.3		Grey medium quartz sand, 10 YR 6/1 (SP)			-45.8	17.5
-48.2	19.4		Grey medium sand and crushed shell, 10 YR 5/1 (SP)		19.0		20
-49.0	20.2		Dark grey muddy sand, 10 YR 4/1 (SM)	100		Composite 12.0-20.0 ft.	
-50.6	21.8		Grey to yellow plastic mud, 10 YR 6/1 & 8/6 (CL)				22.5
						(continued)	