

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1914468.800 Y=84633.100			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-37			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.D.H./E. Olsen			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 11-27-99 11-27-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -27.0 Ft.			
9. TOTAL DEPTH OF HOLE 16.0 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-27.0	.0					-27.0
-28.2	1.2		Brown medium to fine quartz sand, scattered shell fragments. 10 YR 5/2 (SP)		0.5	
-29.2	2.2		Greyish-brown medium to fine quartz sand. 10 YR 6/2 (SP)			
			Brown medium quartz sand. 10 YR 5/3 (SP)	100	4.0	
						-32.0
-34.0	7.0		Light grey-pale brown medium sand, scattered large shell fragments. 10 YR 7/2-7/3 (SP)	100	8.0	
-36.5	9.5		Light grey medium sand. 10 YR 7/1 (SP)			-37.0
-38.5	11.5		Light brown-light grey medium sand, layers of coarse shell fragments. 10 YR 8/2-7/2 (SP)			
-38.7	12.7		Light grey medium sand, scattered large shell fragments. 10 YR 7/1 (SP)	100	14.0	
-43.0	16.0					-43.0 Coarse shell, 15.5-16.0 ft.
						Composite 0-16.0 ft.