

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1901000.000 Y=81500.000			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-44			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 11-28-99 11-28-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -28.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.7 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-28.1	0					-28.1
-29.4	1.3		Light grey fine sand. 10 YR 7/1 (SP)		0.5	
			Light grey fine sand, small shell fragments. 10 YR 7/2 (SP)	100		
					4.0	
-33.0	4.9					-33.1
			Pale brown-grey fine sand, small shell fragments. 10 YR 6/2 (SP)	100		
					8.0	
						-38.1
						Large scallop shell, 10.5 ft
-39.5	11.4					
			White fine sand. 10 YR 8/1 (SP)	100		
					13.0	
-42.2	14.1					
-43.1	15.0		White-pale brown fine sand. 10 YR 8/1-7/3 (SP)			-43.1
-43.9	15.8		Greyish brown shelly sand and mud. 10 YR 4/2			
-44.3	16.2		Light grey sand and shell. 10 YR 8/2 (SW)			
			Yellow-brown fine sand and mud. 10 YR 6/4 (SM)	100		
-46.7	18.6					
-47.8	19.7		Light grey very fine sand, small shell fragments. 10 YR 7/2 (SP)			-47.8
						Composite 0.0-14.0 ft.