

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1910899.600 Y=87570.200				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-4				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-24-99 11-24-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.7 Ft.			
9. TOTAL DEPTH OF HOLE 13.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.7	.0					-26.7	0
			Very pale brown fine sand. 10 YR 8/2 (SP)		0.5		
-28.0	1.3						
			Very light grey fine sand. 10 YR 7/1 (SP)				
-28.8	2.2						
			Grey fine sand. 10 YR 6/1 (SP)	100	3.0		2.5
-31.7	5.0					-31.7	5
			Brownish grey medium to fine sand, scattered shell fragments. 10 YR 6/2 (SP)				
-34.3	7.6				7.0		7.5
			Grey fine sand, some mud, shell fragments. 10 YR 5/1 (SM)	100			
-36.1	9.4						
-36.8	10.1		Dark grey muddy sand. 10 YR 4/1 (SM)			-36.7	10
			Dark grey plastic mud, inclusions of sand, thin layers of sand. 10 YR 4/1 (CL)	100			
-40.2	13.5					-40.2	12.5
							15
							17.5
							20
							22.5
						Composite 0.0-7.0 ft.	