

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1914990.800 Y=81020.100				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-5A				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.8 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.8	0					-28.8	0
							2.5
							5
							7.5
							10
							12.5
-42.3	13.5		Light grey-white medium to fine quartz sand. 10 YR 8/1-7/1 (SP)	100	14.0		15
					16.0	-45.3	
-45.4	16.6		Light grey-pale brown shelly medium sand. Shell fragments 1/8 to 1/2 inch, scattered large whole shells to 2 inches. 10 YR 6/2 (SP)	100	18.0		17.5
-47.4	18.6		Light grey medium to fine quartz sand. 10 YR 7/1 (SP)			-47.8	
-47.6	18.9		Light medium brown shelly sand. 10 YR 7/1 (SP)				20
						Composite 13.5-19.1 ft.	22.5