

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Gulf Shores, AL - Beach Restoration				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1915007.900 Y=83984.300				11. DATUM FOR ELEVATION SHOWN (TBM or MGL) MLLW			
3. DRILLING AGENCY A.O.S.S./Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) C-81				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER C.Dill/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 11-26-99 11-26-99			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.5 Ft.			
9. TOTAL DEPTH OF HOLE 15.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. ZARILLO, SEA, INC			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.5	.0		Pale brown medium to fine sand, scattered shell fragments 1/8-1/2 inch. 10 YR 8/2 (SP)		0.5		0
				100			2.5
-33.3	3.8		Grey medium to fine quartz sand. 10 YR 6/1 (SP)		4.0		
-34.7	5.2		Light brown medium to fine sand, scattered shell fragments 1/8-1 inch. 10 YR 6/3 (SP)			-34.5	5
				100			7.5
-38.0	8.5		Light grey medium to fine sand, scattered shell fragments to 1/2 inch. 10 YR 7/1 (SP)		8.0		
-40.2	10.7		White medium to fine sand. 10 YR 8/1 (SP)			-38.5	10
				100			12.5
-44.6	15.1				14.0	-44.6	15
							17.5
							20
						Composite 0-15.1 ft.	22.5