

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1957461.170 Y=94498.270				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-4				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-2-02 12-2-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.8 Ft.			
9. TOTAL DEPTH OF HOLE 20.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.8	.0					-26.8	0
-28.6	1.8		White to light gray medium to fine quartz sand, abundant white shell fragments in coarse sand to fine gravel range. 10 YR 8.5/0.5-8.5/1 (SP)	100	10		2.5
			White to very light gray medium to fine quartz sand. 10 YR 9/0.5-8.5/1 (SP)		4.0		
				100		-31.8	5
							7.5
-36.6	9.8		Medium gray to light gray fine quartz sand. 10 YR 8.5/0.5-7.5/1 (SP)			-36.8	10
-38.1	11.3		Light gray to white fine quartz sand. 10 YR 8.5/0.5 (SP)		11.0		
-39.7	12.9		Dark gray plastic silt and clay. 10 YR 5.5/0.5-6/0.5 (CL)	100			12.5
						-41.8	15
				100			17.5
-47.1	20.3					Composite 0-11.0 ft.	20
						Final 3/24/03	
							22.5