

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1952957.880 Y=94003.820				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-5				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-2-02 12-2-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.0 Ft.			
9. TOTAL DEPTH OF HOLE 14.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 70 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.0	.0					-26.0	0
			White to very light tannish gray fine quartz sand, scattered white to light tan shell fragments in coarse sand to fine gravel range. 10 YR 9/0.5-8.5/1 (SP)	100	10		2.5
-28.1	3.1		Light gray fine quartz sand. 10 YR 7.5/0.5-7/1 (SP)			-31.0	5
					60		
-33.3	7.3		Medium gray fine quartz sand, some decayed organic matter and silt. 10 YR 6/0.5-7/1 (SP)	100			7.5
-34.9	8.9		Light gray to medium gray fine quartz sand, trace of silt. 10 YR 7.5/0.5-7/1 (SP)			-36.0	10
					110		
-37.9	11.9		Medium to light gray fine quartz sand, some silt. 10 YR 7/1 (SP)	100			12.5
-38.0	13.0		Gray silty fine quartz sand. 10 YR 7/1 (SM)			-40.1	15
-39.6	13.6		Light tannish gray fine quartz sand. 10 YR 7.5/0.5 (SP)				
-40.7	14.1		Gray plastic silt and clay. 10 YR 6/0.5 (CL)				17.5
							20
							22.5
Composite 0-11.0 ft.							
Final 3/24/03							