

DRILLING LOG		DIVISION		INSTALLATION	
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE		SHEET 1 OF 1	
2. LOCATION (Coordinates or Station) X=1956496.190 Y=90013.460		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-7		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-02-02 12-02-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -31.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.4 Ft.		18. TOTAL CORE RECOVERY FOR BORING 93 %			
		19. SIGNATURE OF G. Zarillo, SEA, Inc.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-31.7	.0					-31.7
-32.6	.9		Very light tannish gray fine quartz sand, trace of shell fragments in fine gravel range. 10 YR 8.5/1 (SP)			
-35.0	3.3		Gray to light gray fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 7.5/0.5-7/0.5 (SP)	100		
-37.0	5.3		Tannish gray fine quartz sand, trace of brown silt, few large whole shells in coarse gravel range, trace of gray clay in collapsed burrows. 10 YR 7.5/1-7/1.5 (SP)			-36.7
-38.2	7.5		Light gray fine quartz sand, trace of gray to brown silt in collapsed burrows. 10 YR 8/0.5 (SP)	100		
			Dark gray silt and clay. 10 YR 5.0/0.5 (CL)			
				100		-41.7
				100		-46.7
-50.1	18.4					-50.1
						No samples
						Final 5/22/03