

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1949011.470 Y=89016.140				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-8R1-R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-02-02 12-02-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.2 Ft.			
9. TOTAL DEPTH OF HOLE 22.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.2	.0					-25.2	0
-25.8	.6		Light tannish gray fine quartz sand, trace of gray shell fragments in fine gravel range. 10 YR 8/1 (SP)				
			Light gray fine quartz sand, trace of dark gray shell fragments in fine to medium gravel range. 10 YR 8/0.5 (SP)	100			2.5
-31.4	6.2					-30.2	5
			Gray to light tannish gray fine quartz sand, scattered whole shells and shell fragments in medium to coarse gravel range. 10 YR 8/1-7.5/1.5 (SP)	100			7.5
-33.5	8.3						
			Tan fine quartz sand, trace of silt. 10 YR 7/2 (SP)				
-35.6	10.4					-35.2	10
			Gray to brownish gray silty fine quartz sand. 10 YR 6/2 (SM)	100			12.5
						-40.2	15
							17.5
-44.3	19.1			100			
			Brownish-gray silt, clay and sand. 10 YR 6/1.5 (ML)			No Samples	20
-45.4	20.2					Final 5/22/03	
			Brownish-gray silt and sand, very abundant shell fragments. 10 YR 6/1.5 (ML)				
-47.5	22.3					-47.5	22.5