

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1947004.570 Y=90040.010				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-9				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-02-02 12-02-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.2 Ft.			
9. TOTAL DEPTH OF HOLE 17.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 88 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.2	.0					-24.2	0
-25.4	1.2		Very light tan fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 8.5/1 (SP)				
			Very light gray to tannish orange gray fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 8.5/0.5-8.5/3 (SP)	100			2.5
						-28.2	5
-32.0	7.8		Light gray fine quartz sand, trace of shell fragments in fine gravel range. 10 YR 8/0.5 (SP)	100			7.5
-34.5	10.3		Light tannish gray fine quartz sand, trace of brown silt. 10 YR 8/1.5-7.5/2.5 (SP)			-34.2	10
				100			12.5
-38.7	14.5		Tan fine quartz sand, some silt. 10 YR 7.5/2.5 (SP)			-38.2	15
-40.8	16.6		Tannish gray silty quartz sand. 10 YR 7/2-7/3 (SM)	100		-41.7	17.5
-41.7	17.5						
						Composite 0-13.0 ft.	20
						Final 7/8/03	
							22.5