

DRILLING LOG		DIVISION		INSTALLATION		
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE		SHEET 1 OF 1		
2. LOCATION (Coordinates or Station) X=1945977.520 Y=91006.750		11. DATUM FOR ELEVATION SHOWN (FBM or MSL) MLW				
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE				
4. HOLE NO. (As shown on drawing title and file number) BC-10		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0				
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2				
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER				
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-02-02 12-02-02				
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -25.2 Ft.				
9. TOTAL DEPTH OF HOLE 16.7 Ft.		18. TOTAL CORE RECOVERY FOR BORING 84 %				
		19. SIGNATURE OF G. Zerillo, SEA, Inc.				
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-25.2	.0					-25.2
-26.9	1.7		Very light gray to white fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100		
			Light gray fine quartz sand, scattered gray, tan and white shell fragments in medium to coarse gravel range. 10 YR 8.5/0.5-8/1 (SP)	100		
						-30.2
-34.5	9.3		Tannish gray fine quartz sand, trace of brown silt. 10 YR 8/1-7.5/1.5 (SP)	100		-35.2
-38.5	13.3		Brownish gray silty fine quartz sand, some clay. 10 YR 7/1.5-6.5/2 (SM)	100		
-38.3	14.1		Gray silt and abundant gray to white shell fragments. 10 YR 5.5/0.5 (ML)	100		-40.2
-41.3	16.1		Gray clay. 10 YR 4.5/0.5 (CL)	100		-41.8
-41.9	16.7					
						Composite 0-10.0 ft.
						Final 7/8/03