

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1944986.240 Y=92016.590				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-12				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-2-02 12-2-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.9 Ft.			
9. TOTAL DEPTH OF HOLE 20.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 99 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.9	.0					-25.9	0
-28.1	2.2		Light tannish gray fine quartz sand, trace of gray shell fragments in fine gravel range. 10 YR 8.5/4.5 (SP)	100	3.0		2.5
-30.5	4.6		Light gray fine quartz sand, trace of gray shell fragments, trace of dark gray silt in collapsed burrow structures. 10 YR 7.5/0.5 (SP)				
-32.0	6.1		Gray silty sand. 10 YR 6/0.5 (SM)			-30.9	5
-35.7	9.8		Dark gray clay and abundant large whole shells and shell fragments. 10 YR 5/0.5 (CL)	100			7.5
-38.0	13.1		Dark gray silty and clayey sand, very large whole shells. 10 YR 5/0.5 (SM)	100		-35.9	10
-41.8	15.9		Dark gray to gray silty quartz sand, some clay. 10 YR 5/0.5-6/0.5 (SM)			-40.9	15
-46.1	20.2		Brownish gray to gray silty sand. 10 YR 5/0.5-6/2 (SM)	100			17.5
						No composite	20
						Final 5/1/03	
							22.5