

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1947020.640 Y=95006.940				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-13				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-2-02 12-2-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.3 Ft.			
9. TOTAL DEPTH OF HOLE 16.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 81 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.3	.0		Tan to light tan fine quartz sand, shell fragments and whole shells in fine to medium gravel range. 10 YR 8/1.5-7.5/1.5 (SP)		10	-27.3	0
-28.6	2.3		Tannish gray fine quartz sand, some silt. 10 YR 7/1-7/1.5 (SP)	100			2.5
-31.4	4.1		Gray silty fine quartz sand, shell fragments and whole shells in fine to medium gravel range. 10 YR 6/0.5 (SM)			-32.3	5
				100			7.5
						-37.3	10
-38.2	11.9		Gray clay and silt, shell fragments in fine gravel range. 10 YR 6/0.5 (CL)	100			12.5
						-42.3	15
-43.5	16.2			100		-43.5	
							17.5
							20
						Final 5/13/03	22.5