

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1949511.320 Y=97002.430				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-14				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-2-02 12-2-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -8.8 Ft.			
9. TOTAL DEPTH OF HOLE 19.7 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zariko, SEA, Inc.			

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-8.8	.0					-8.8	0
			Light tan medium quartz sand, trace of silt and clay in burrow structures. 10 YR 8.5/1.5 (SP)				
-11.2	2.4		Light gray medium to fine quartz sand. 10 YR 8/0.5 (SP)	100	10		2.5
-12.5	3.7						
-13.0	4.2		Light tannish gray fine quartz sand, abundant shell fragments in coarse sand to fine gravel range. 10 YR 8/1.5 (SP)			-13.8	5
			Very light gray fine quartz sand. 10 YR 8.5/0.5 (SP)				
				100	8.0		7.5
						-18.8	10
-20.9	12.1		Light gray fine quartz sand, trace of silt in collapsed burrows. 10 YR 8/0.5 (SP)	100		-23.8	15
					16.0		
-26.1	17.3		Tannish gray fine quartz sand, inclusions of brown silt in burrow structures. 10 YR 7.5/0.5-7.5/1.5 (SP)	100			17.5
-28.1	19.3					-28.5	20
-28.5	19.7		Dark gray clay. 10 YR 5.5/0.5 (CL)			Composite 0-16.0 ft.	
			Tan fine quartz sand. 10 YR 7.5/2 (SP)			Final 5/1/03	