

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1927182.960 Y=89387.630				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-16				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-3-02 12-3-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -17.5 Ft.			
9. TOTAL DEPTH OF HOLE 18.9 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				18. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-17.5	.0					-17.5	0
-18.9	1.4		Light tan to white medium to fine quartz sand, trace of shell fragments in fine to medium gravel range. 10 YR 8.0/2-8.5/0.5 (SP)				
			White medium to fine quartz sand, few scattered white to gray shell fragments in fine gravel range. 10 YR 8.5/0.5-8/0.5 (SP)	100			2.5
						-22.5	5
				100			7.5
-27.8	10.3		Very light gray fine quartz sand, trace of silt and clay in collapsed burrow structures. 10 YR 8/0.5-8.5/0.5 (SP)			-27.5	10
-30.2	12.7			100			12.5
			White to very light tannish gray medium to fine quartz sand. 10 YR 8.5/0.5-8/1.5 (SP)			-32.5	15
				100			17.5
-36.4	18.9					-36.4	
						Composite 0-18.0 ft.	20
						Final 4/15/03	
							22.5