

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1928983.780 Y=88509.440			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-17			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-3-02 12-3-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -19.4 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-19.4	.0					-19.4
-20.9	1.5		Light tan medium to fine quartz sand, abundant large whole shells and shell fragments in fine gravel range. 10 YR 8.5/3 (SP)			Large whole shell at 1.4 ft.
			White medium to fine quartz sand, scattered tan to white whole shells and shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100	10	
-26.2	6.8					-24.4
			White to light gray medium to fine quartz sand, gray, tan and white large whole shells and shell fragments in fine to coarse gravel range. 10 YR 8.5/0.5 (SP)	100	8.0	
-28.5	9.1					-28.4
			White medium to fine quartz sand, trace of shell fragments, trace of clay. 10 YR 9/0.5 (SP)	100		
						-34.4
-37.1	17.7					Thin plastic layer at 16.3 ft.
				100	16.0	
-38.0	18.6		Tan to brown medium to fine quartz sand, clay inclusions and trace of silt. 10 YR 6.5/2.5 (SP)			-38.0
						Composite 0-16.0 ft.
						Final 4/15/03