

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1930980.970 Y=87516.030				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-18				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-3-02 12-3-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.5 Ft.			
9. TOTAL DEPTH OF HOLE 18.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.5	.0					-24.5	0
-26.5	2.0		White medium to fine quartz sand, trace of silt and clay in burrow structures. 10 YR 8.5/0.5-9/0.5 (SP)	100			2.5
-28.0	3.5		Light gray to medium gray medium to fine quartz sand. 10 YR 7/0.5-8.5/0.5 (SP)	100			5
			White fine quartz sand, inclusions of minor silt and clay in collapsed burrow structures. 10 YR 8.5/0.5-9/0.5 (SP)	100		-29.5	7.5
				100		-34.5	10
				100		-38.5	15
-41.3	16.8		Brownish gray fine quartz sand, some silt. 10 YR 6.5/1.5-7/1.5 (SP)	100		Thin peat layer at 17.1 ft.	17.5
-42.6	18.1					-42.6	20
						Composite 0-16.0 ft.	22.5
						Final 5/1/03	