

Hole No. BC-20

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1931007.320 Y=86535.160			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-20			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-3-02 12-3-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -29.4 Ft.			
9. TOTAL DEPTH OF HOLE 16.8 Ft.			18. TOTAL CORE RECOVERY FOR BORING 99 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-29.4	.0		Very light gray medium to fine quartz sand, scattered gray to white shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100	3.0	-29.4
-34.4	5.0		Brownish gray silty quartz sand. 10 YR 6.5/1.5 (SM)			-34.4
-34.7	5.3		Very light gray fine quartz sand and shell fragments in fine gravel range. 10 YR 8/0.5 (SP)			
-35.0	5.6		Dark gray clay. 10 YR 5.5/0.5 (CL)	100		
-37.7	8.3		Gray silt and some fine quartz sand. 10 YR 6/0.5 (ML)			-38.4
-42.1	12.7		Medium gray to light gray fine quartz sand, some silt and clay in collapsed burrow structures. 10 YR 7/0.5-7.5/0.5 (SP)	100		
-44.5	15.1		Very light gray to white medium to fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100		-44.4
-46.2	16.8					-46.2
						Final 5/1/03