

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1929983.280 Y=87545.090				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-21				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-3-02 12-3-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -22.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-22.0	.0					-22.0	0
-23.7	1.7		White to very light tan medium to fine quartz sand, scattered tan to white shell fragments in fine to medium gravel range, worm tubes. 10 YR 8.5/1-8.5/1.5 (SP)	100	10		
			Light gray medium to fine quartz sand, scattered shell fragments in fine to medium gravel range, trace of silt and clay in burrow structures. 10 YR 7.5/0.5 (SP)	100		Prominant burrow structure at 4.0-4.3 ft	
						-27.0	5
-30.1	8.1			100	8.0		7.5
			Very light gray medium to fine quartz sand, trace of silt and clay in collapsed burrow structures. 10 YR 8.5/0.5 (SP)				
-31.8	9.9					-32.0	10
			White medium to fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)				
-33.7	11.7			100			12.5
			Light gray to medium gray fine quartz sand, trace of brown silt. 10 YR 7.5/0.5-7/0.5 (SP)				
-36.0	14.0						
-36.4	14.4		Brownish gray fine quartz sand, trace of silt. 10 YR 7/1 (SP)		15.0	-37.0	15
			Very light gray medium to fine quartz sand. 10 YR 8.5/0.5-8/0.5 (SP)				
-37.8	15.9			100			17.5
			Light gray to medium gray fine quartz sand, thin layers of dark gray silty sand. 10 YR 7.5/0.5-7/0.5 (SP)				
-40.4	18.4					-40.4	17.5
						Composite 0-15.0 ft.	20
						Final 4/15/03	
							22.5