

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1930024.750 Y=88520.370			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-22			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-3-02 12-3-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -23.2 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-23.2	.0					-23.2
-24.0	.8		Very light gray to white fine quartz sand, shell fragments and whole shells in fine to medium gravel range. 10 YR 8.5/0.5 (SP)			
			Very light gray to white fine quartz sand. 10 YR 8.5/0.5 (SP)	100		
-27.1	3.9					Layer of large white shell
			Medium gray medium to fine quartz sand, some brown silt. 10 YR 7/0.5-7/1.5 (SP)			fragments at 4.5-4.6 ft.
-28.5	6.3					-28.2
-30.5	7.3		Gray to brownish gray silty quartz sand, some gray clay. 10 YR 8.5/0.5-6.5/2 (SM)	100		
			White fine quartz sand, inclusion of gray silty sand. 10 YR 8.5/0.5 (SP)			
-32.4	9.2					
-33.1	9.9		Dark gray silt. 10 YR 5.5/0.5 (ML)			-33.2
			Gray clay and few thin layers of light gray fine quartz sand. 10 YR 5.5/0.5 (CL)	100		
-37.6	14.4					
-38.3	15.1		Very light gray to white fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)			-38.2
-38.3	16.1		Dark gray clay and thin layers of quartz sand. 10 YR 5.5/0.5 (CL)			
			White fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100		
-41.2	18.0					
-42.3	19.1		Gray clay and thin layers of white quartz sand. 10 YR 5.5/0.5 (CL)			-42.3
						Composite 0-4.0 ft.
						Final 5/1/03