

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1927020.290 Y=87018.940				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-24				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-03-02 12-03-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -22.9 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
19. SIGNATURE OF G. Zarillo, SEA, Inc.							
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-22.9	.0					-22.9	0
			Light tannish gray to white fine quartz sand, few large shell fragments and whole shells in coarse gravel range. 10 YR 8.5/0.5-8.5/1 (SP)	100	10		2.5
-25.8	2.9		Light gray fine quartz sand, few scattered shell fragments in coarse sand to fine gravel range. 10 YR 8/0.5 (SP)			-27.9	5
-28.5	5.6		White fine quartz sand. 10 YR 9/0.5 (SP)	100	8.0		7.5
					12.0	-32.9	10
				100		-37.9	15
-38.5	15.6		Very light gray fine quartz sand. 10 YR 8.5/0.5 (SP)	100		-41.5	17.5
-41.5	18.6						20
						Composite 0-17.0 ft.	
						Final 3/24/03	
							22.5