

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1926018.220 Y=86025.080				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-25				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-03-02 12-03-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.7	.0					-25.7	0
-26.3	.6		Light tan to light gray fine quartz sand. 10 YR 8/0.5-8/1.5 (SP)				
			Gray-light gray medium to fine quartz sand, scattered gray shell fragments in medium to coarse gravel range. 10 YR 7.5/0.5 (SP)	100	10		2.5
-28.8	3.8		Gray silty sand. 10 YR 7/0.5 (SM)			-30.7	5
			Gray to tannish fine quartz sand, scattered gray to white shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/1-7.5/2 (SP)				
-32.8	7.2		Light gray to light tannish gray fine quartz sand. 10 YR 7.5/0.5-7.5/1.5 (SP)	100	8.0		7.5
-34.3	8.6		Very light gray to light gray fine quartz sand, scattered inclusions of decayed organic matter. 10 YR 7.5/0.5-8/0.5 (SP)			Large whole shell at 8.4 ft.	
						-35.7	10
				100	12.0		12.5
						-40.7	15
-43.8	18.1			100		-43.8	17.5
						Composite 0-16.0 ft.	20
						Final 3/24/03	
							22.5