

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1928009.660 Y=86033.150				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-26				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-03-02 12-03-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.7	.0					-24.7	0
			White fine quartz sand, scattered white to light gray shell fragments in coarse sand to medium gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100	10		2.5
-27.6	2.9		Light gray fine quartz sand, abundant white to gray shell fragments in coarse sand to fine gravel range, scattered white to gray whole shells in medium gravel range. 10 YR 7.5/0.5 (SP)			-29.7	5
-30.9	6.2		White fine quartz sand, few scattered shell fragments in fine to medium gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100	80		7.5
						-34.7	10
-36.5	11.8		Light gray to white fine quartz sand, few inclusions of decayed organic matter, trace of white shell fragments. 10 YR 8/0.5-8.5/0.5 (SP)	100	120		12.5
						-39.7	15
				100			17.5
-43.1	18.4					-43.1	18.4
						Composite 0-18.0 ft.	20
						Final 3/24/03	20
							22.5