

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1926028.140 Y=87026.880				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-29				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-03-02 12-03-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.0 Ft.			
9. TOTAL DEPTH OF HOLE 19.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.0	.0					-24.0	0
-26.4	2.4		Light gray fine quartz sand. 10 YR 8/0.5 (SP)	100	10		2.5
-29.2	5.2		Light gray to medium gray fine quartz sand, scattered gray shell fragments in fine to coarse gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100	8.0	Large whole shell at 3.3 ft.	5
-32.6	8.6		Very light gray fine quartz sand, scattered decayed organic matter in burrow walls. 10 YR 8/0.5 (SP)	100			7.5
-33.9	9.9		Light gray to brownish gray fine quartz sand. 10 YR 7.5/0.5-7/1.5 (SP)	100			10
-43.0	19.0		Very light gray to light tannish gray fine quartz sand. 10 YR 8.5/0.5-8.5/1 (SP)	100	16.0		12.5
							15
							17.5
							20
						Composite 0-18.0 ft.	
						Final 6/24/03	
							22.5