

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1961515.010 Y=96467.600			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-31			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -19.8 Ft.			
9. TOTAL DEPTH OF HOLE 18.3 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-19.8	.0		White fine quartz sand scattered large whole gray shells and shell fragments in fine to medium gravel range. 10 YR 9/0.5 (SP)	100	10	-19.8
-27.2	7.4		Light gray to medium gray medium to fine quartz sand, abundant gray to white shell fragments in fine gravel range, few scattered large shell fragments in medium to coarse gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100	8.0	-24.8
-30.2	10.4		Light gray to light tannish gray medium to fine quartz sand, few scattered shell fragments in fine gravel range, trace of brown silt in collapsed burrows. 10 YR 7/0.5-7.5/1 (SP)	100	16.0	-29.8
-38.1	18.3			100		-34.8
						-38.1
						Composite 0-17.0 ft.
						Final 5/1/03