

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X-1960471.770 Y-96482.550				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-32				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -21.2 Ft.			
9. TOTAL DEPTH OF HOLE 17.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 95 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-21.2	.0					-21.2	0
			Light gray to light tannish gray fine quartz sand, trace of white to light gray shell fragments in fine to medium gravel range. 10 YR 8/0.5-8/1 (SP)	100	10		2.5
-26.0	4.8					-26.2	5
			Light gray medium to fine quartz sand, abundant white, tan, and light gray shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/0.5 (SP)	100	8.0		7.5
-29.8	8.6					-31.2	10
			White medium to fine quartz sand, scattered inclusions of gray silt and clay in collapsed burrow structures. 10 YR 9/0.5 (SP)	100			12.5
						-36.2	15
				100	16.0		17.5
-38.8	17.6					-38.8	17.5
						Composite 0-17.0 ft.	20
						Final 5/1/03	22.5