

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE		
2. LOCATION (Coordinates or Station) X=1960451.430 Y=97509.890		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW		
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE		
4. HOLE NO. (As shown on drawing title and file number) BC-34		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0		
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER		
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02		
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -18.6 Ft.		
9. TOTAL DEPTH OF HOLE 19.9 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %		
		19. SIGNATURE OF G. Zarillo, SEA, Inc.		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-18.6	0					-18.6	0
			White to very light tannish gray fine quartz sand few scattered shell fragments in fine gravel range, occasional large shell fragment in coarse gravel range. 10 YR 8.5/0.5-8.5/1 (SP)	100	10		2.5
-23.6	5.0					Large tan shell fragment at 4.5 ft. -23.6	5
			Light gray fine quartz sand, trace of shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)				7.5
-25.8	7.2			100	8.0		10
			Medium gray to light gray medium to fine quartz sand, abundant shell fragments in fine to medium gravel range. 10 YR 7/0.5-7.5/0.5 (SP)				12.5
				100		-28.6	15
-32.8	14.3				15.0	-33.6	17.5
			Tan to tannish gray medium to fine quartz sand, trace of gray silt in burrow structures. 10 YR 7.5/1-7.5/2 (SP)	100			20
-38.5	19.9					Composite 0-19.0 ft. -38.5	22.5
						Final 5/1/03	