

DRILLING LOG			DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1961479.250 Y=95490.530				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-36				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -22.9 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			

  

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-22.9	.0					-22.9
-24.7	1.8		Very light gray to white fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 8.5/0.5 (SP)	100	10	
-26.3	3.4		Light gray to light tannish gray fine quartz sand, scattered white to tan shell fragments and whole shells in fine to medium gravel range. 10 YR 8/0.5-8/1.5 (SP)	100		
			Medium gray to light gray medium to fine quartz sand. 10 YR 7/0.5-7.5/0.5 (SP)			-27.8
-31.1	8.2		White medium to fine quartz sand, trace of silt and clay in burrow structures. 10 YR 8.5/0.5-9/0.5 (SP)	100	8.0	
				100		-32.8
						-37.8
-41.5	18.6			100	16.0	
						-41.5
Composite 0-18.0 ft.						
Final 5/1/03						