

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1955983.090 Y=93013.730				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-37				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.9 Ft.			
9. TOTAL DEPTH OF HOLE 17.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 95 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.9	.0					-27.9	0
-28.7	.8		Light gray fine quartz sand, scattered gray to light gray whole shells and shell fragments in coarse sand to medium gravel range. 10 YR 7.5/1-7.5/1.5 (SP)				
			White fine quartz sand, scattered inclusions of decayed organic matter. 10 YR 8.5/0.5-9/0.5 (SP)	100	10		2.5
-32.9						-32.9	5
-35.2	7.3						
-36.1	8.2		White to very light gray fine quartz sand, scattered gray organic inclusions. 10 YR 8.5/0.5-8/0.5 (SP)	100	8.0		7.5
			Very light gray to light gray fine quartz sand, scattered gray inclusions of organic matter. 10 YR 7.5/0.5-8/0.5 (SP)			-37.9	10
					12.0		12.5
-42.9						-42.9	15
-45.1	17.2						
-45.7	17.8		Gray fine quartz sand, crushed shell material and silt. 10 YR 6.5/1 (SM)	100		-45.7	17.5
						Composite 0-15.0 ft.	20
						Final 3/24/03	22.5