

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1954982.880 Y=92979.730			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-38			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -28.3 Ft.			
9. TOTAL DEPTH OF HOLE 17.7 Ft.			18. TOTAL CORE RECOVERY FOR BORING 95 %			
19. SIGNATURE OF G. Zarillo, SEA, Inc.						

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-28.3	.0		White fine quartz sand. 10 YR 8.5/0.5-9.0/0.5 (SP)	100	10	-28.3
-34.1	5.8		Very light gray to white fine quartz sand. 10 YR 8.0/0.5-8.5/0.5 (SP)	100	8.0	-33.3
-41.0	12.7		Light gray fine quartz sand, scattered shell fragments in fine gravel range. 10 YR 8.0/0.5 (SP)	100	12.0	-36.3
-43.1	14.8		Light gray fine quartz sand, abundant white shell fragments in coarse sand to medium gravel range. 10 YR 8.0/0.5-7.5/0.5 (SP)	100		-43.3
-44.8	16.5		Shell fragments and matrix of gray quartz sand. 10 YR 7.0/0.5 (SW)			-46.0
-46.0	17.7		Gray plastic silt and clay. 10 YR 6/0.5 (CL)			
						Composite 0-15.0 ft.
						Final 3/24/03