

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1956009.200 Y=91973.360				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-39				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 4 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.5 Ft.			
9. TOTAL DEPTH OF HOLE 19.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.5	.0					-30.5	0
-31.5	1.0		Light tannish gray to white fine quartz sand, abundant shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/0.5-8.5/1.5 (SP)	100	10		2.5
			Very light gray to white medium to fine quartz sand, scattered inclusions of decayed organic matter. 10 YR 8/0.5-8.5/0.5 (SP)		40		
						-35.5	5
-38.0	7.5		Light gray to white medium to fine quartz sand. 10 YR 8/0.5-8.5/0.5 (SP)	100			7.5
					10.0		10
-42.8	12.4		Gray to light gray fine quartz sand. 10 YR 7.5/0.5-7/0.5 (SP)	100			12.5
					16.0		15
-48.6	18.1		Gray silty quartz sand, abundant tan shell fragments. 10 YR 7/0.5-6.5/0.5 (SM)	100			17.5
-49.7	19.2					-49.7	20
						Composite 0-16.0 ft.	
						Final 6/24/03	
							22.5