

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1955989.430 Y=93981.240				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-41				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-6-02 12-6-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.7 Ft.			
9. TOTAL DEPTH OF HOLE 19.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.7	.0					-27.7	0
-29.3	1.6		Light gray medium to fine quartz sand, scattered whole shells and shell fragments in coarse sand to coarse gravel range. 10 YR 7.5/0.5-7.5/1 (SP)	100	10		2.5
			White to very light gray medium to fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100	8.0		7.5
				100		-32.7	5
				100		-37.7	10
				100		-42.7	15
-44.5	16.8		Light gray fine quartz sand. 10 YR 7.5/0.5-7.5/1 (SP)	100	16.0		17.5
-45.6	17.9		Gray medium to fine quartz sand. 10 YR 7/0.5 (SP)				
-46.2	18.5		Light gray fine quartz sand. 10 YR 7.5/1.0 (SP)				
-47.2	19.5					-47.2	20
						Composite 0-16.0 ft.	
						Final 3/24/03	
							22.5