

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1956973.820 Y=92995.580				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-42				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-06-02 12-06-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.0 Ft.			
9. TOTAL DEPTH OF HOLE 19.7 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.0	.0					-29.0	0
-29.6	.6		Light tannish gray few large gray shell fragments in medium gravel range, worm tubes. 10 YR 8/1.5 (SP)				
			Light gray fine quartz sand, few scattered inclusions of decayed organic matter. 10 YR 8.5/0.5 (SP)	100	10		2.5
-34.0	5.0		White to light gray medium to fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100	8.0	-34.0	5
							7.5
-39.5	10.5		Light gray to medium gray fine quartz sand. 10 YR 7.5/0.5-7/0.5 (SP)	100	12.0	-39.0	10
							12.5
-42.8	13.8		Dark gray plastic clay and silt. 10 YR 5.5/0.5 (CL)	100		-44.0	15
							17.5
-48.7	19.7					-48.7 Composite 0-12.0 ft.	20
						Final 3/24/03	22.5