

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1847311.960 Y=72806.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-44				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -22.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
19. SIGNATURE OF G. Zerillo, SEA, Inc.							
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-22.1	.0					-22.1	0
			Light tannish gray fine quartz sand, scattered tan and gray whole shells in medium gravel range, trace of gray shell fragments in fine gravel range. 10 YR 8/1 (SP)	100			2.5
-25.7	3.6					-27.1	5
			Light gray fine quartz sand, some medium quartz sand, scattered gray to dark gray whole shells in medium gravel range, trace of shell fragments in fine gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100			7.5
						-32.1	10
				100			12.5
						-37.1	15
-38.0	15.9						17.5
			Light tannish gray fine quartz sand, some medium quartz sand, trace of shell fragments in fine to medium gravel range. 10 YR 7/0.5-7.5/1.5 (SP)	100			
-41.3	19.2					-41.3	20
						Composite 0-17.0 ft.	
						Final 5/13/03	
							22.5