

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1852481.560 Y=74509.340				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-45				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.7 Ft.			
9. TOTAL DEPTH OF HOLE 18.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.7	.0		Light gray medium to fine quartz sand, abundant gray to white shell fragments in fine to medium gravel range. 10 YR 7.0/0.5-7.5/0.5 (SP)	100	10	-25.7	0
-33.5	7.8		Light gray to very light gray medium to fine quartz sand, trace of gray to white shell fragments, trace of silt and clay in burrow structures. 10 YR 7.5/0.5-8/0.5 (SP)	100	8.0	-30.7	2.5
-41.8	16.1		Tan fine quartz sand, some silt. 10 YR 6/2.5 (SP)	100	15.0	-35.7	5
-43.5	17.8		Tan to brown silty quartz sand. 10 YR 5.5/3-6/3 (SM)	100		-40.7	7.5
-44.5	18.8					-44.5	10
						Composite 0-15.0 ft.	12.5
						Final 4/15/03	15
							17.5
							20
							22.5