

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1861502.610 Y=76007.630				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-47				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-7-02 12-7-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.4 Ft.			
9. TOTAL DEPTH OF HOLE 19.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 97 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.4	.0					-28.4	0
			Light tannish gray fine quartz sand, trace of brown silt in burrow structures, scattered gray whole shells and shell fragments in medium gravel range. 10 YR 7.5/1 (SP)	100			2.5
						-33.4	5
				100			7.5
-36.7	8.3		Gray silty fine quartz sand, abundant large whole shells in medium to coarse gravel range. 10 YR 6.5/0.5 (SM)			-38.4	10
-39.2	10.8		Dark gray silty quartz sand, scattered large whole shells and shell fragments. 10 YR 5/0.5 (SM)	100			12.5
						-43.4	15
				100			17.5
-47.7	19.3					-47.7	20
						Composite 0-6.0 ft.	
						Final 5/13/03	
							22.5